

BLANK PAGE



IS 7951 : 2003 ISO 8116-7 : 1995

भारतीय मानक

वस्त्रादि मशीनरी एवं सहायकांग — आवलन के बीम — सलाइवर, रोविंग तथा यार्न के रंजन के लिए बीम

(दूसरा पुनरीक्षण)

Indian Standard

TEXTILE MACHINERY AND ACCESSORIES — BEAMS FOR WINDINGS — BEAMS FOR DYEING SLIVERS, ROVINGS AND YARNS

(Second Revision)

ICS 59.120.20

© BIS 2003

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

NATIONAL FOREWORD

This Indian Standard (Second Revision) is identical with ISO 8116-7: 1995 'Textile machinery and accessories — Beams for winding — Part 7: Beams for dyeing slivers, rovings and yarns' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on the recommendations of the Dyeing, Finishing and Allied Machinery and Accessories Sectional Committee and approval of the Textile Division Council.

This standard has been revised to bring it in line with ISO 8116-7: 1995 since the earlier version of IS 7951 was based on ISO 1037: 1982 which has been replaced by ISO 8116-7: 1995.

The text of ISO Standard has been approved as suitable for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear referring to this standard, they should be read as 'Indian Standard'.
- b) Comma (,) has been used as a decimal marker in the International Standard while in Indian Standards, the current practice is to use a point (.) as the decimal marker.

IS 7951 : 2003 ISO 8116-7 : 1995

Indian Standard TEXTILE MACHINERY AND ACCESSORIES — BEAMS FOR WINDINGS — BEAMS FOR DYEING SLIVERS, ROVINGS AND YARNS

(Second Revision)

1 Scope

This part of ISO 8116 defines the basic terms and designation, and lays down the main dimensions as the driving devices for perforated beams used for dyeing slivers, rovings or yarns.

2 Terminology and main dimensions

(See figures 1 and 2 and table 1)

- d_1 outside diameter of flange
- d_2 outside diameter of barrel
- d_3 diameter of axial orifice
- b distance between the flanges

IS 7951: 2003 ISO 8116-7: 1995

Dimensions in millimetres




Figure 1 — Beam with simple flanges and driving device — Type A (One lug per flange)

Dimensions in millimetres

X

40 ±0.5

A0 ±0.5

Figure 2 — Beam with flanges and counter shoulder, and driving device — Type B (One key per flange)

IS 7951: 2003 ISO 8116-7: 1995

NOTE 1 For type A and type B, it is possible to have one lug or one key per flange (according to the values of d_2 and d_3).

Table 1 — Main dimensions

Dimensions in millimetres

Туре	d ₁		d_2		r	<i>b</i>	d ₃
	nominal	tolerance	nominal	tolerance		± 1	± 0,3
	300	± 0,5	150	± 1,2	96	1 400 1 600 1 800	145
Α	(480)	± 0,8	230	± 1,2	137,5		
	520						225
	(520)	± 0,8	280	± 1,2	_		
В	600						
В	600		360	± 2	_		
	750		500				
NOTE — Th	1	entheses show		whenever no	ssible		

NOTE — The values in parentheses should be avoided whenever possible.

3 Designation

The designation of a dyeing beam in accordance with this part of ISO 8116 shall include the following information in the order given:

- a) "Dyeing beam";
- b) reference to this part of ISO 8116, i.e. ISO 8116-7;
- c) the type of beam (A or B);
- d) the flange diameter, d_1 , in millimetres;
- e) the barrel diameter, d_2 , in millimetres;
- f) the distance between the flanges, b, in millimetres.

EXAMPLE

A dyeing beam, type B, with flange diameter d_1 of 600 mm, diameter of barrel d_2 of 280 mm and distance between flanges b of 1 400 mm is designated as follows:

Dyeing beam ISO 8116-7 — B 600 \times 280 \times 1 400

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc: No. TX 21 (0490).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected
-		
	BUREAU OF INDIAN STANDAR	DS
Headquarters:		
Manak Bhavan, 9 Bahadur S Telephones: 2323 0131, 232	Telegrams: Manaksanstha (Common to all offices)	
Regional Offices:		Telephone
Central: Manak Bhavan, 9 NEW DELHI 1100	$ \begin{cases} 23237617 \\ 23233841 \end{cases} $	
Eastern: 1/14 C. I. T. Schen KOLKATA 700 05	{2337 8499,2337 8561 2337 8626,2337 9120	
Northern: SCO 335-336, Sec	\begin{cases} 603843 \\ 609285 \end{cases}	
Southern : C. I. T. Campus, l	{2254 1216, 2254 1442 2254 2519, 2254 2315	
Western: Manakalaya, E9 I MUMBAI 400 09	$\begin{cases} 28329295, 28327858\\ 28327891, 28327892 \end{cases}$	

Branches: AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.

FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM.

VISAKHAPATNAM.